

# Alimentatore DC30V con 150W

## PSU 30V 150W IP67



### Product features

Questo alimentatore è adatto per il funzionamento commutabile di moduli LED a tensione controllata. Con una tensione di uscita di 30 V, è in grado di generare una potenza di uscita di 150 W. Grazie al suo design compatto e compatto, può essere installato idealmente in diversi scenari applicativi e soddisfa i requisiti per il grado di protezione IP67.



<b>durata</b>	>62.000 ore
<b>Temperatura ambiente</b>	-25 ... +50°C
<b>Temperatura di stoccaggio e trasporto</b>	-40 ... +80°C
<b>voltaggio nominale</b>	AC 230 V Intervallo: AC 90 - 264VCC 127-370 V
<b>Frequenza nominale</b>	50/60Hz Intervallo: 47 - 63 Hz
<b>il peso</b>	1,15 kg
<b>Materiale della custodia</b>	metallo
<b>Classe di protezione</b>	IO.
<b>Classe di protezione</b>	IP67

<b>Tipo di connessione</b>	fine linea libero
----------------------------	-------------------

### Dimensions

Width (B)	Height (H)	Length (L)
68 mm	39 mm	228 mm

### Further product features

Due to the constant further development and improvement of LED technology, changes are possible  
 © InstaLighting GmbH, Technical changes reserved 2.2021  
 InstaLighting GmbH, InstaLighting GmbH, Hohe Steinert 10, 58509 Lüdenscheid, Deutschland  
 Telephone: + 49 2351 65619-0, info@instalighting.de, www.instalighting.de

# Alimentatore DC30V con 150W

## PSU 30V 150W IP67



### Additional Information

[www.instalighting.de](http://www.instalighting.de)